

















Product Range

Normal & Light Weight (Lava Pumice) Concrete Blocks

(Hollow, Solid, Hourdi & Thermal Insulated Block)

TYPE	SIZE (inch)	DIMENSIONS (mm)		
		LENGTH	WIDTH	HEIGHT
 Hollow Block	10	400	250	200
	8	400	200	200
	8	400	190	200
	8	390	190	190
	6	400	150	200
	6	400	140	200
	6	390	140	190
	4	400	100	200
	4	390	100	190
	4	390	90	190
 Solid Block	10	400	250	200
	8	400	200	200
	8	390	190	190
	6	400	150	200
	6	390	140	190
	4	400	100	200
	4	390	100	190
 Styrol Insulated Blocks	8	400	200	200
	10	400	250	200
 Hourdi Blocks	6	380 - 420	150	200
	8	380 - 420	200	200
	8	360 - 400	200	200
	10	380 - 420	250	200
	10	360 - 400	250	200
	12	380 - 420	300	200
	12	360 - 400	300	200
	13	350 - 370	340	200
	14	380 - 420	350	200

Concrete Paving Blocks

TYPE OF PAVER	WORK SIZE (mm)
Uni - Coloc 	100
Uni - Shape 	80 60
Uni - Starter 	80 60
Rectangular 	200 × 100 × 80 200 × 100 × 60
Behaton 	80 60
Quadro (I) shape 	80 60
Octagon 	80 60
Rhombus 	80 60
Cube 	80 60
Heel Kerb Stone 	600 × 150 × 75